
Institutional swivel castor 100 mm, TPE, ball bearing, bolt hole 10.2 mm, 70 kg, product code 44831

Institutional swivel castor with thermoplastic rubber (TPE) tread, wheel diameter 100 mm, on ball bearing. It carries 70 kg dynamic and 80 kg static, fixed with a 10.2 mm bolt hole.





Drawing number **2-7LG-20K** | Product code **44831** | EAN **3838461448317**

Type	Institutional swivel castor
Wheel diameter	100 mm
Wheel width	24 mm
Tread	thermoplastic rubber (TPE) tread, 82 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	ball bearing
Load capacity, dynamic	70 kg
Load capacity, static	80 kg
Fitting	single bolt hole
Hole diameter	10.2 mm
Overall height	123 mm
Offset	30 mm
Weight	0.37 kg
Temperature, continuous	-20 to +60 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	32 mm
Tread material	Polyethylene

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Dust-proof and leaves no trail on the floor. Turns easily. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.