Institutional swivel castor 100 mm, polypropylene, ball bearing, bolt hole 12 mm, 85 kg, product code 44889

Institutional swivel castor with a 100 mm wheel, solid polypropylene wheel, on ball bearing. It carries 85 kg dynamic and 100 kg static, fixed with a 12 mm bolt hole.



Drawing number **2-813** | Product code **44889** | EAN **3838461448898**

Type	Institutional swivel castor
Wheel diameter	100 mm
Wheel width	30 mm
Tread	solid polypropylene wheel, 60±5 Shore D
Tread colour	grey
Wheel centre	polypropylene
Bearing	ball bearing
Load capacity, dynamic	85 kg
Load capacity, static	100 kg
Fitting	single bolt hole
Hole diameter	12 mm
Overall height	130 mm
Offset	35 mm
Weight	0.6 kg
Temperature, continuous	-20 to +60 °C
Top plate size	61 mm
Tread hardness	60 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Dust-proof and leaves no trail on the floor. Turns easily. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.