Wheel 125 mm, heat-resistant polyamide, plain bearing, axle hole 12 mm, 200 kg, product code 44909

Wheel with heat-resistant solid polyamide wheel, wheel diameter 125 mm, on plain bearing. It carries 200 kg dynamic and 250 kg static, with a 12 mm axle hole.



Drawing number **2-762 ISO** | Product code **44909** | EAN **3838461449093**

Type	Wheel
Wheel diameter	125 mm
Wheel width	38 mm
Tread	heat-resistant solid polyamide wheel, 85±5 Shore D
Wheel centre	heat-resistant polyamide
Bearing	plain bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Axle hole	12 mm
Weight	0.27 kg
Temperature, continuous	-25 to +250 °C
Temperature, short exposure (max. 10 min)	-40 to +300 °C
Fitting	Wheel hub
Hub length	45 mm
Tread material	Heat resistant polyamide
Tread hardness	85 Shore D

Properties and use

Built for heat and used in bakeries. The continuous and short-term temperatures are in the table. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.