
Heavy duty swivel castor 160 mm, cast iron, ball bearing, plate 140x110 mm, 600 kg, Art. 2-152-32K

Heavy duty swivel castor, 160 mm wheel diameter, cast iron tread, running on ball bearing. Rated load is 600 kg dynamic, 750 kg static, mounted on a 140x110 mm top plate with hole distance 105x80 mm.





Drawing number **2-152-32K** | SKU **56392** | EAN **3838461563928**

Type	Heavy duty swivel castor
Wheel diameter	160 mm
Wheel width	50 mm
Tread	cast iron tread, 180-220 180-220 HB
Wheel centre	cast iron
Bearing	ball bearing
Load capacity, dynamic	600 kg
Load capacity, static	750 kg
Top plate	140x110 mm
Hole distance	105x80 mm
Fixing hole diameter	11 mm
Overall height	200 mm
Offset	54 mm
Directional lock	optional
Weight	4.65 kg
Temperature, continuous	-40 to +130 °C
Temperature, short exposure (max. 10 min)	-40 to +130 °C

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Wears slowly and rolls with low resistance. Large temperature changes are no problem. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.