Wheel 100 mm, black rubber, plain bearing, axle hole 12 mm, 80 kg, Art. 2-123 ISO

Wheel with black rubber tread, wheel diameter 100 mm, on plain bearing. It carries 80 kg dynamic and 100 kg static, with a 12 mm axle hole.



Drawing number **2-123 ISO** | SKU **62372** | EAN **3838461623721**

Type	Wheel
Wheel diameter	100 mm
Wheel width	32 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	steel, zinc electroplated, Cr(VI)-free
Bearing	plain bearing
Load capacity, dynamic	80 kg
Load capacity, static	100 kg
Axle hole	12 mm
Weight	0.25 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub
Hub length	44 mm

Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Steers easily and copes with uneven floors and obstacles. Steel rim and rubber tyre make a strong wheel. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.