Wheel 200 mm, pneumatic tyre, roller bearing, axle hole 20 mm, 60 kg, product code 64097

Wheel with grey pneumatic tyre, wheel diameter 200 mm, on roller bearing. It carries 60 kg dynamic and 70 kg static, with a 20 mm axle hole.



Drawing number **2-633 ISO** | Product code **64097** | EAN **3838461640971**

Type	Wheel
Wheel diameter	200 mm
Wheel width	50 mm
Tread	grey pneumatic tyre
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	60 kg
Load capacity, static	70 kg
Axle hole	20 mm
Weight	0.43 kg
Temperature, continuous	-5 to +60 °C
Temperature, short exposure (max. 10 min)	-5 to +60 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Leaves no marks on the floor. Suited to uneven ground, and the pneumatic tyre cushions shocks. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.