Wheel 150 mm, polyamide, roller bearing, axle hole 20 mm, 300 kg, product code 66701, wheel centre black

Wheel with solid polyamide wheel, wheel diameter 150 mm, on roller bearing. It carries 300 kg dynamic and 370 kg static, with a 20 mm axle hole.



Drawing number **2-753 ISO** | Product code **66701** | EAN **3838461667015**

Type	Wheel
Wheel diameter	150 mm
Wheel width	46 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Axle hole	20 mm
Weight	0.45 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Fitting	Wheel hub
Hub length	58 mm
Tread hardness	70 Shore D

Properties and use

Polyamide resists many chemicals, carries high loads and takes shock impact. It tolerates large temperature swings. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.