Wheel 200 mm, pneumatic tyre, plain bearing, axle hole 20 mm, 75 kg, product code 91044

Wheel with a 200 mm wheel, grey pneumatic tyre, on plain bearing. It carries 75 kg dynamic and 90 kg static, with a 20 mm axle hole.



Drawing number **2-501 ISO** | Product code **91044** | EAN **3838461910449**

Type	Wheel
Wheel diameter	200 mm
Wheel width	50 mm
Tread	grey pneumatic tyre
Wheel centre	steel, zinc electroplated, Cr(VI)-free
Bearing	plain bearing
Load capacity, dynamic	75 kg
Load capacity, static	90 kg
Axle hole	20 mm
Weight	0.6 kg
Temperature, continuous	-5 to +60 °C
Temperature, short exposure (max. 10 min)	-5 to +60 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Passes obstacles gently and leaves the floor unmarked. Suited to crushed stone ground. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.