Wheel 160 mm, black rubber, plain bearing, axle hole 20 mm, 180 kg, product code 91052

Wheel with black rubber tread, wheel diameter 160 mm, on plain bearing. It carries 180 kg dynamic and 220 kg static, with a 20 mm axle hole.



Drawing number **2-947 ISO** | Product code **91052** | EAN **3838461910524**

Type	Wheel
Wheel diameter	160 mm
Wheel width	40 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	180 kg
Load capacity, static	220 kg
Axle hole	20 mm
Weight	0.7 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.