# Wheel 200 mm, black rubber, plain bearing, axle hole 20 mm, 230 kg, Art. 2-948 ISO

Wheel, 200 mm wheel diameter, black rubber tread, running on plain bearing. Rated load is 230 kg dynamic, 280 kg static, with a 20 mm axle hole.



Drawing number **2-948 ISO** | SKU **91054** | EAN **3838461910548**

| | |
|---|---|
| **Type** | Wheel |
| **Wheel diameter** | 200 mm |
| **Wheel width** | 50 mm |
| **Tread** | black rubber tread, 80 Shore A |
| **Tread colour** | black |
| **Wheel centre** | polypropylene |
| **Bearing** | plain bearing |
| **Load capacity, dynamic** | 230 kg |
| **Load capacity, static** | 280 kg |
| **Axle hole** | 20 mm |
| **Weight** | 1.4 kg |
| **Temperature, continuous** | -20 to +70 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +80 °C |
| **Fitting** | Wheel hub |
| **Hub length** | 58 mm |

Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

## Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.